

JBF SERIES 4-DIE 4-BLOW BOLT FORMER (四模四沖螺絲成型機)



SPECIFICATION 規格/機型	MODEL	JBF 5B4S	JBF 7B4S	JBF 7B4SXL	JBF 10B4S	JBF 10B4SL	JBF 13B4S	JBF 13B4SL	JBF 13B4SXL	JBF 13B4SUL	JBF 17B4S	JBF 17B4SL	JBF 17B4SXL	JBF 17B4SUL	JBF 19B4S	JBF 19B4SL	JBF 19B4SXL	JBF 19B4SEL	JBF 19B4SUL	
FORGING STATION 模數		4																		
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)		3	5		8		10			12				15						
CUT-OFF LENGTH MAX. 最大切斷長度 (mm)		35	55	80	70	105	105	130	180	220	135	180	230	350	140	185	240	310	400	
KICK-OUT LENGTH MAX. 後托頂出長度 (mm)		32	45	75	60	90	90	120	175	215	115	175	225	325	120	180	225	280	325	
P.K.O. LENGTH MAX. 前托頂出長度 (mm)		8	10	17	13	20	20	23	30	34	20	30	36	60	26	30	35	60	60	
CUT-OFF QUILL (DxL) 切模 (mm)		18x25	20x30	20x50	28x46	28x46	35x56	38x79	38x79	38x79	40x66	40x80	40x80	40x80	46x80	46x80	60x100	60x100	65x100	
MAIN DIE HOLE (DxL) 母模 (mm)		28x45	38x60	38x85	50x65	50x105	60x105	70x135	70x185	70x240	70x135	80x185	80x240	80x330	80x123	93x190	93x240	93x294	93x350	
DIES PITCH 母模中心距離 (mm)		36	48		60		87			93				114						
PUNCH HOLE (DxL) 公模束 (mm)		24x45	32x60	32x90	40x80	40x110	45x110	45x111	45x130	45x175	50x111	50x130	50x190	50x200	60x120	60x170	60x200	60x232	60x250	
RAM STROKE 主滑板行程 (mm)		80	100	140	120	150	150	200	250	350	180	250	360	460	200	270	360	420	500	
FORGING POWER 壓造力 (ton)		10	20	25	40	40	65	65	70	70	85	85	90	90	120	120	130	130	130	
PRODUCTS 產品	SIZE 尺寸	1/8(M3)	3/16 (M4)		1/4 (M6)		5/16 (M8)			3/8 (M10)				1/2 (M12)						
	MAX.L 最長長度 (mm)	25	40	65	50	75	75	100	150	200	100	150	200	300	100	150	200	250	300	
	MIN.L (mm) 最短長度	HEX. 外六角螺絲	8	10	12	12	16	16	20	30	40	16	30	50	100	20	40	50	50	100
		SOCKET 強力螺絲	10	12	16	16	20	20	25	40	40	20	40	50	100	25	40	50	50	100
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)		250	300	250	300	240	240	210	180	140	200	175	110	80	170	125	100	90	80	
MAIN MOTOR 主馬達 (hp)		5	10	15	15	15	20	30	30	30	30	40	40	40	50	50	50	50	50	
APPROX. WT. 機械重量 (ton)		3	4.5	6	8	10	12	13.5	15.5	19.5	16	19	24	29	23	27	32	35	39	

0709-2011

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE. (本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄規格僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE. (設備產能依產品之形狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度。)

JBF SERIES 4-DIE 4-BLOW BOLT FORMER (四模四沖螺絲成型機)



SPECIFICATION 規格/機型		MODEL	JBF 24B4S	JBF 24B4SL	JBF 24B4SXL	JBF 24B4SUL	JBF 24B4SULL	JBF 30B4S	JBF 30B4SL	JBF 30B4SUL	JBF 30B4SULL	JBF 33B4S	JBF 36B4SS	JBF 36B4S	JBF 36B4SL	JBF 36B4SXL	JBF 41B4S	JBF 45B4S
FORGING STATION 模數			4															
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)			18				23				26	29				34	38	
CUT-OFF LENGTH MAX. 最大切斷長度 (mm)			185	270	320	400	420	270	320	400	445	300	220	320	370	460	400	450
KICK-OUT LENGTH MAX. 後托頂出長度 (mm)			185	230	280	335	380	230	285	335	370	260	185	290	340	410	340	390
P.K.O. LENGTH MAX. 前托頂出長度 (mm)			33	36	50	60	70	35	60	60	70	45	30	60	60	60	60	70
CUT-OFF QUILL (DxL) 切模 (mm)			60x100	60x120	60x120	60x120	60x120	75 x 120				84x130	90 x 140				110x140	115x140
MAIN DIE HOLE (DxL) 母模 (mm)			100x195	100x240	100x294	100x360	100x420	125x240	125x294	125x360	125x420	145x280	160x210	160x294	160x370	160x450	178x385	195x420
DIES PITCH 母模中心距離 (mm)			126				138				156	174				195	210	
PUNCH HOLE (DxL) 公模束 (mm)			75x160	75x200	75x232	75x232	75x270	90x197	90x232	90x240	90x290	96x210	105x180	105x232	105x235	106x270	120x250	135x280
RAM STROKE 主滑板行程 (mm)			280	360	420	500	580	360	430	500	580	400	300	440	500	600	500	580
FORGING POWER 壓造力 (ton)			200	200	215	215	250	265	285	300	320	320	360	380	420	450	520	635
PRODUCTS 產品	SIZE 尺寸		5/8 (M16)				3/4 (M20)				7/8 (M22)	1 (M24)				1-1/8 (M27)	1-3/4 (M30)	
	MAX.L 最長長度 (mm)		150	200	250	300	360	200	250	305	360	225	150	250	300	380	300	355
	MIN.L (mm) 最短長度	HEX. 外六角螺絲	25	50	60	100	100	40	60	100	100	50	40	60	100	100	100	100
		SOCKET 強力螺絲	35	50	60	100	100	60	60	100	100	60	50	60	100	100	100	100
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)			120	100	75	65	60	100	70	60	55	80	80	60	55	45~50	45	40~45
MAIN MOTOR 主馬達 (hp)			75	75	100	100	100	100	125	125	125	125	125	125	150	150	175	200
APPROX. WT. 機械重量 (ton)			45	51	56	62	68	65	76	87	98	85	86	108	128	160	152	195

0709-2011

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE. (本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄規格僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE. (設備產能依產品之形狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度。)